


Senkschrauben

mit Nase und 6kt.-Mutter - Stahl 8.8




DIN 604

d	M 10	M 12	M 16	M 20
b	26	30	38	46
d _k Hilfsmaß	19	24	32	32
k	5,5	7	9	11,5
l				
25	46,07	65,96		
30	45,97	63,40		
35	48,73	47,24		
40	52,66	49,14	169,75	290,93
45	54,71	75,67		
50		67,49	172,82	309,84
60		75,67	183,55	337,45
70		86,41	197,36	355,86
80		102,77	242,35	371,71
Paketinhalt	100 >45: 50	50	50 >45: 25	25

Senkschrauben

mit Vierkantansatz und 6kt.-Mutter
Stahl 8.8 und 10.9



DIN 608

d	M 10	M 12	M 16	7/16 UNF	M 12
b	26	30	38		30
Festigkeitsklasse	8.8	8.8	8.8	8.8	10.9
d _k Hilfsmaß	19	24	32		24
l					
25	32,21	49,14			
30	30,98	45,91		76,18	81,81
35	35,79	47,24		79,25	74,65
40	37,32	49,29	199,92	83,34	82,83
45	40,34	54,20	207,58	88,45	96,12
50	42,80	59,31	207,58	94,59	85,90
60	55,73	62,38	219,86	114,53	68,51
70		73,11	247,98		82,83
80		83,85	277,12		108,91
90		107,88	290,41		
100		126,80	314,44		
Paketinhalt	100 >45: 50	50	50 >45: 25	50	50